

Generator Technical Data	
Genset Model:	TAD1343GE
Brand:	Volvo
Output Type:	AC, 400V, 50Hz, 1500rpm, 3 phase, 0.8 lagging
Power:	304kw/380kva
Output Frequency:	50Hz
Rated Current (A):	547
Cooling System:	Water Cooling
Silent Type Gross Weight :	3800kg
Silent Type Dimension:	4000*1650*2150mm
Voltage available on request:	50Hz: 380, 400, 415, V / 220, 230, 240V 60Hz: 220, 380, 416, 440, 480V / 110, 208, 220, 240V
Standard Configuration:	1, Cooling Fan with fan guard and front guard 2, Alternator: Single bearing ,IP23,H class 3, 24V Charger 4, Shock Absorber 5, Dry Air Filter, Fuel Filter, Engine Oil Filter. 6, Smartgen 6110N Automatic System 7, 2x 12v Start Battery with connecting cable 8, Storage Battery and battery line, Exhaust pipe, Corrugated pipe for anti-vibration, Cone Tube, Flange, Muffler 9, Silent Type 10, Documents
Alternator Parameter	
Brand:	Stamford
Model:	S4L1D-F41
Excitation:	Single Bearing, Brushless, Self-excitation
Phase:	3 phase
Connection:	3phase 4wire
Rated Voltage:	400V
Frequency and speed:	50HZ/1500RPM
Power:	304kw/380kva
Bearing Number:	1
Power Factor:	0.8
Protection Class:	IP23
Voltage Regulation:	≤+/-0.5%
Tel. Harmonic Factor THF:	≤2%
Tel. Influence Factor TIF:	≤50
Altitude Condition:	≤1000M
Others:	circuit breaker, AVR

Engine Parameter	
Brand:	Volvo
Engine Model:	TAD1343GE
Output Type:	1500rpm 24V Electricity Starting
Aspiration:	turbo-charged
Power:	356kw
Cylinders:	6
Bore * Stroke:	110*135mm
Fuel System at 100% load	195g/kwh
Filter	Dry Air Filter, Fuel Filter, Engine Oil Filter
vibration damper	each foot has Shock Absorber; Load Range: 1000-1100kgf; damping ratio: 0.8C/Cc; working temperature: -40 to +70°C
Others:	Storage Battery and battery line, Exhaust pipe, Corrugated pipe for anti-vibration, Cone Tube, Flange, Muffler
Standard Specification	
Cooling Method:	water radiator, belt drive cooling fan with fan shield
General Feature:	exhaust muffler, starter battery , fittings, operators and service manual, etc.
Control System:	Smartgen Automatic Control System 1, Function: Control Panel provides necessary Monitoring, Control and Protection functions for the diesel genset. 2, Installation: Free-standing, fully enclosed dust-tight design, having concealed hinges and locking handle. 3, Generator Protections :a: Low oil pressure, b: Over temp. c: Over/low speed d:Charger failure e:Over crank f:Stop failure g:Low/high charge voltage h:Emergency i:Common alarm j:Generating failure

