

Dynapac D30T

Highway pavers



- Lower TCO with rugged design and extended wear parts life
- Award winning Mat Master screed for high quality results
- Simplified smart paving with Dynapac PaveManager
- iTrack system providing excellent traction & reliability
- Innovative solutions for non-stop paving (Safe Impact, Fail Safe heating)
- Designed and built in USA for North American Market

Technical Data

 Masses	
Weight	16.91 t
Tractor weight including Mat Master screed	20.50 t

 Capacity	
Transport width	3.37 m
Total length	6.70 m
Transport height	3.04 m
Max working width	9.14 m
Basic screed width	3 m
Placement thickness (max)	305 mm

 Undercarriage	
Track length	2.88 m
Track width	0.45 m
Drive	Hydrostatic final drive, integrated in track frame
Paving speed	up to 74.9 m/min
Transport speed	up to 15.8 km/hr

 Operation	
Operator console	Dual Swing out operator consoles
Dashboard	2 fully functional tractor consoles with display

 Engine	
Manufacturer/Model	Cummins QSB 6.7
Rated power	168 kW @ 2200 rpm
Emissions according to	Tier 4f
Electrical system	12 V / 130 Amp
Fuel tank capacity	318 l

 Material hopper	
Capacity	14 t
Hopper width	3.37 m
Dumping height	559 mm

 Conveyor	
Conveyor type	Dual bar feeder
Conveyor width	2 X 565 mm
Conveyor control	2 independent conveyors with proportional speed control

 Auger	
Auger diameter	432 mm
Auger control	2 reversible augers with proportional speed control
Auger height adjustment	Hydraulic

Find us locally at www.dynapac.us

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.


dynapac_d30t_en-20220221.115142.pdf 2022-02-21 11:51

Dynapac D30T


Highway pavers



Technical Data



Dimensions	
A. Axle track	2870 mm
B1. Width, max.	3366 mm
B2. Width, standard	3366 mm
B3. Width, center of tracks	2438 mm
H1. Height, max.	3416 mm
H2. Height, transport	3048 mm
H3. Height Dumping	559 mm
L1. Length	6706 mm
L3. Length, hopper	2032 mm
C1. Track width	457 mm



Suitable screeds						
Model	Basic width	Hydr.Extendable up to	Working width, max.	Compacting elements	Heating system	Weight
Mat Master 20R	3.05 ft	6.09 m	9.14 m	Vibration	Electric	3583 lbs

Find us locally at www.dynapac.us

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.