A WIRTGEN GROUP COMPANY

HAMM

Technical data

HD 10 VT



Tandem rollers Series HD CompactLine | **H262**

Tandem roller with vibration drum and set of wheels

HIGHLIGHTS

> Ergonomic driver platform
> Simple, intuitive and language-neutral operation
> Compact dimensions
> Good visibility of drum edge, machine and jobsite surroundings
> Easy transport, simple loading

TECHNICAL DATA HD 10 VT (H262)

Weights		
Operating weight with ROPS	kg	2385
Max. operating weight	kg	3110
Axle load, front/rear	kg	1210/1175
Static linear load, front	kg/cm	12,1
French classification, value/class		12,1/PV2
Machine dimensions		
Total length	mm	2530
Total height with ROPS	mm	2475
Height loading, min.	mm	1752
Centre distance	mm	1700
Total width	mm	1110
Maximum working width	mm	1050
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2470
Drum dimensions		
Drum width, front	mm	1000
Drum diameter, front	mm	720
Drum thickness, front	mm	15
Drum type, front		Smooth/non-split
Track offset, left/right	mm	0/50
Tyre dimensions		
Tyre size, rear		205/60-R15
Width over tyres, rear	mm	1000
Number of tyres, rear		4
Diesel engine		
Manufacturer		KUBOTA
Model		D1503
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		22,9/31,1/2700
Power SAE J1349, kW/HP/rpm		22,9/30,7/2700
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust emissions category, Brazil		MAR 1
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 12,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, level I/II	Hz	65/51
Amplitude, front, level I/II	mm	0,45/0,45
Centrifugal force, front, level I/II	kN	43/26
Steering		
Pendulum angle +/-	°	8
Steering, type		Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure

Tank capacity/filling capacity		
Fuel tank, capacity	L	42
Water tank, capacity	L	180
Additive tank, capacity	L	18
Sound level		
Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with access from both sides | Drive lever, left and right | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Central lifting bracket | Plastic scraper, folding

OPTIONAL EQUIPMENT

Equipment Management | Edge pressing and cutting device | Track indicator | Water drain valve | All-wheel lock | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Working spotlights | Towing eye, front | Tow hitch | V-belt protection

HAMM AG • Hammstr. 1 • D-95643 Tirschenreuth • Tel +49 9631 80-0 • Fax +49 9631 80-111 • www.hamm.eu
Further data on request/subject to change Illustrations may contain optional features.© **Hamm AG** 2026 - 2615452 en-GB V9