A WIRTGEN GROUP COMPANY

HAMM

Technical data

HD 12 VV



Tandem rollers Series HD CompactLine | **H262**

Tandem roller with two vibration drums

HIGHLIGHTS

> Good visibility of drum edge, machine and jobsite surroundings
> Compact dimensions
> Ergonomic driver platform
> Simple, intuitive and language-neutral operation
> Easy transport, simple loading

TECHNICAL DATA HD 12 VV (H262)

Weights		
Operating weight with ROPS	kg	2695
Max. operating weight	kg	3410
Axle load, front/rear	kg	1335/1360
Static linear load, front/rear	kg/cm	11,1/11,3
French classification, value/class		11,3/PV3
Machine dimensions		
Total length	mm	2530
Total height with ROPS	mm	2475
Height loading, min.	mm	1752
Centre distance	mm	1700
Total width	mm	1310
Maximum working width	mm	1250
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2370
Drum dimensions		
Drum width, front/rear	mm	1200/1200
Drum diameter, front/rear	mm	720/720
Drum thickness, front/rear	mm	15/15
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50
Diesel engine		
Manufacturer		KUBOTA
Model		D1503
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		22,9/31,1/2700
Power SAE J1349, kW/HP/rpm		22,9/30,7/2700
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust emissions category, Brazil		MAR 1
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 12,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, level I/II	Hz	65/51
Vibration frequency, rear, level I/II	Hz	65/51
Amplitude, front, level I/II	mm	0,45/0,45
Amplitude, rear, level I/II	mm	0,45/0,45
Centrifugal force, front, level I/II	kN	49/30
Centrifugal force, rear, level I/II	kN	49/30
Steering		
Pendulum angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capacity		
Fuel tank, capacity	L	42
Water tank, capacity	L	180
Sound level		
Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with access from both sides | Drive lever, left and right | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, folding | Equipment Management | Edge pressing and cutting device | Track indicator | Water drain valve | All-wheel lock | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Working spotlights | Towing eye, front | Tow hitch | V-belt protection

Further data on request/subject to change Illustrations may contain optional features.© **Hamm AG** 2026 - 2615453 en-GB V9